

Make a LASTING IMPRESSION...

...with COPPER PRESS FITTINGS from Jones Stephens.

Our durable, quality copper press fittings provide water and air tight sealing on industrial, commercial and residential applications. Save time, labor and money.

Now that's the lasting impression you want to leave with your customers.



SPECIFICATIONS | PRODUCT FEATURES

- ✓ EPDM O-ring with circumferential leak track
- ✓ Water & air tight, creating a leakproof joint when correctly pressed
- ✓ For use with copper tubes in: hard temper, half hard temper and soft temper
- ✓ Operating Pressure - 200 PSI Max
- ✓ Test Pressure – 600 PSI Max
- ✓ Low Pressure Steam – 15 PSI Max
- ✓ Vacuum 24.5" Mercury Max @ 68°F
- ✓ Operating Temperature 0°F-250°F
- ✓ Approved Applications:
Hot & Cold Potable Water
Hydronic Heating (with Glycol)
Chilled Water
Compressed Air (200 PSI Max)
Non-medical Gases (140 PSI Max)
- ✓ Meets Approvals:
NSF International, ASME B 16.51-2011, CSA International, CRN Listed (Canada), UPC/IPC by IAPMO, MASS Approval
- ✓ Lead Free Compliant



Press tool for demonstration only. Product not offered by Jones Stephens.

COMPATIBILITY | PRESS TOOLS

Requires "v-profile" jaw sets.

Milwaukee M12 Compact Jaws 1/2" to 1-1/4"
Milwaukee M18 Standard Jaws 1/2" to 2"
Nibco Standard Jaws 1/2" to 2"
REMS Compact Jaws 1/2" to 1-1/4"
REMS Standard Jaws 1/2" to 2"
Ridgid Tool Compact Jaws 1/2" to 1-1/4"
Ridgid Tool Standard Jaws 1/2" to 2"

Rothenberger Compact Jaws 1/2" to 1"
Rothenberger Standard Jaws 1/2" to 2"
Stanley Virax Copper Jaws 1/2" to 2"
Milwaukee M18 Standard Jaws 2-1/2" to 4"
REMS Standard Pressing Ring 2-1/2" to 4"
Ridgid Tool Standard Jaw for Copper Press 2-1/2" to 4"

Visit www.jonesstephens.com for a complete SKU listing.



A World and Main company

AVAILABLE COPPER PRESS FITTINGS





COUPLINGS (SOCKETS)
WITH ROLLED TUBE STOP, P X P

COUPLINGS (SOCKETS) LESS STOP, P X P




REDUCERS, P X P

FITTING REDUCERS, P X FTG



45° ELBOWS, P X P

45° STREET ELBOWS, P X FTG





90° ELBOWS, P X P

90° STREET ELBOWS, P X FTG





TEES, P X P X P

FEMALE ADAPTERS, P X FPT




FEMALE FITTING ADAPTERS, FTG X FPT

MALE ADAPTERS, P X MPT



MALE FITTING ADAPTERS, FTG X MPT

CAPS, P



A World and Main company

South 3249 Moody Parkway • Moody, AL 35004 | North 50 Keystone Blvd. East • Pottsville, PA 17901 | West 28624 Witherspoon Parkway • Valencia, CA 91355

Contact Us: Phone 800-355-6637 | Fax 800-462-6991 | Web www.jonesstephens.com